

# LIVE1202



PRODUCT OVERVIEW - v1

## PROFESSIONAL 12-CHANNEL/2-BUS MIXER

- > 7 XLR INPUTS WITH DNA™ MICROPHONE PREAMPS
- > DYNAMIC COMPRESSION (CHANNELS 1-4)
- > 3-BAND EQ PLUS 2 AUX SENDS PER CHANNEL



### SPECIFICATIONS

#### Mono Input Channels

Microphone inputs:	Electronically balanced, discrete input configuration
Frequency response:	20 Hz to 20 kHz, +0.5 dB
THD+N:	<0.02% at 0 dBu, 1 kHz
Gain range:	0 dB to 50 dB (Mic)
SNR:	90 dB

#### Line Inputs

	Electronically balanced
Frequency response:	20 Hz to 20 kHz, +0.5 dB
THD+N:	<0.03% at 0 dBu, 1 kHz
Sensitivity range:	-15 dBu to 30 dBu

#### Impedances

Microphone inputs:	51.1 K $\Omega$
Channel insert return:	200 K $\Omega$
All other inputs:	>100 K $\Omega$
2-Track outputs:	10 K $\Omega$
All other outputs:	20 K $\Omega$

#### Equalization

High-shelving:	$\pm 15$ dB @ 12 kHz
Mid-bell (mono):	$\pm 15$ dB @ 2.5 kHz
Low-shelving:	$\pm 15$ dB @ 80 Hz
Main EQ:	9 EQ bands (63 Hz, 125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz, 16 kHz), $\pm 15$ dB

#### DSP Section (DFX)

A/D & D/A converters:	24-bit
DSP Resolution:	24-bit
Effects:	10 DSP effects families with 10 variations available per family
Presets:	100 total
Controls:	Rotary encoder to select preset, DSP mute switch, peak LED indicator

#### Main Mix

Noise (bus noise):	Fader 0 dB, channels muted: -64 dBr (ref: +4 dBu) Fader 0 dB, all input channels assigned & set to unity gain: -64 dBr (ref: +4 dBu)
Phantom Power:	Mic Pin2/Pin3 and Pin1 47 $\pm$ 2V

#### Power Supply

Main voltage:	USA/Canada: 100-120 VAC ~60 Hz UK/Australia: 240 VAC ~50 Hz Europe: 210-240 VAC ~50 Hz
Power consumption:	50 W
Fuse:	1.25 A
Main connection:	Standard IEC receptacle

Dimensions (w x d x h)	14.1" x 13.6" x 3.1" / 358 mm x 346 mm x 80 mm
------------------------	--

Weight	9.0 lbs. / 4.1 kg
--------	-------------------



### APPLICATIONS

- Small/Mid-sized PA systems
- Gymnasiums, fitness centers, and dance studios
- Houses of worship
- Theaters
- Bars, restaurants, clubs
- Band and Mobile DJ systems
- Special events, presentations, and weddings


### FEATURES

- 7 XLR inputs with high- DNA™ mic preamps
- Dynamic compression (Channels 1-4)
- 3-band EQ plus 2 aux sends per channel
- 60mm faders with mute switch and LED meters
- USB audio connectivity with level control
- 100 Alesis DSP effects
- Balanced XLR, balanced/unbalanced 1/4" outputs
- 9-band graphic EQ for main or monitor outputs
- Headphone out with independent level control
- USB jack to power lamps or charge mobile devices

## DIMENSIONS



## CONNECTORS



# LIVE1202

altoprofessional.com

All information subject to change. Page 2