

## AUDAC

## Features

- Tough steel chassis, 19-inch rackmount design
- Designed to use with the Q4 amplifier
- Four channels of 4 Ohm 600 Watt to 100, 70 or 50 Volts



## Applications

- Conference spaces
- Retail stores
- Hotels
- Restaurants
- Multimedia projects
- Churches

The AUDAC Q4TR is a line transformer unit especially designed to be used in combination with the AUDAC Q4 power amplifier.

This line transformer ensures that the 4 Ohm loudspeaker outputs of the AUDAC Q4 amplifier are transformed for 50, 70 and 100 Volt applications.

The Q4TR features 4 independent mono channels with a maximum input of 600 Watt at 4 Ohm.

The output per channel is rated at:

- 100 V(16,66 Ohm)
- 70 V(8,16 Ohm)
- 50 V(4,16 Ohm)

The connectors are all located on the back of the Q4TR unit. Every channel has a Speakon input connector, and a 8 pole screw clamp output connector where the desired output signal can be selected.

The Q4TR line transformer unit has a steel 19" rack mount chassis with a height of 2 HE.

## ► Specifications

SYSTEM SPECIFICATIONS	
RMS Power @ 4 Ohm	4 x 600 W
Input impedance	20 Kohm balanced
	10 Kohm unbalanced
Power supply	240 V AC / 50-60 Hz
Line transformer 1	100 V - 25 Ohm
Line transformer 2	70 V - 12.25 Ohm
Line transformer 3	50 V - 6.25 Ohm
PRODUCT FEATURES	
Dimensions (Width x Height x Depht)	482 x 88 x 405 mm
Weight net	32 Kg
Mounting	19"
Unit height	2 HE
Construction	Steel
Colour	Black
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight and volume	35.2 Kg - 0.0483 Cbm

\*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products