



Features

- 60 Watt power rating
- Flexible system
- 11 attenuation steps of 3dB
- Built in relay for priority signals
- Slim design
- Blends beautifully into walls
- Easy installation

Applications

- Private houses
- Industrial buildings
- Offices
- ...

The VC3062 is a 100 Volt volume controller capable of handling a power up to 60 Watt.

The volume is adjustable with a rotatable dial in 11 steps of 3 dB.

It is equipped with a relay and separate input for the reception of 24V priority signals. This means that when a priority signal occurs, the volume will be automatically switched to maximum level.

This can be very useful for emergency and evacuation messages.

Due to it's slim and good looking design, these volume controls will blend into all kinds of different environments or interiors.

The construction is made of sturdy ABS and therefore suitable for big projects in industrial buildings as well as standard home interiors.

The dimensions are 80 mm x 80 mm, and a builtin depth of 46 mm is required.

The connections are made at the back with screw terminal blocks.





► Specifications

SYSTEM SPECIFICATIONS	
Max power handling	60 W
Max. operation voltage	100 V
Attenuation	11 x 3 dB
Priority relay	24 V - 25 mA
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	80 x 80 x 50 mm
Built-in depth	46 mm
Weight net	340 g
Construction	ABS
Colour	White
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	370 g - 0.0008Cbm

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our product