

# NEW CSE HH 5e PUR

CAT 5e cable suitable for audio networks  
and for EtherSound™ systems.

- highflex, resilient, reelable
- PUR jacket for mobile indoor/outdoor applications
- Plugs: 2x RJ 45 HIROSE® TM31
- Data category: CAT 5e (100 MHz)
- S/UTP AWG 26/19



| ITEM NO. | MATCH CODE                     | LENGTH |
|----------|--------------------------------|--------|
| 15532    | CSE 0,3 HH 5e PUR; 0,3m, black | 0,3 m  |
| 15533    | CSE 0,5 HH 5e PUR; 0,5m, black | 0,5 m  |
| 15534    | CSE 1 HH 5e PUR; 1m, black     | 1 m    |
| 15535    | CSE 1,5 HH 5e PUR; 1,5m, black | 1,5 m  |
| 15536    | CSE 2 HH 5e PUR; 2m, black     | 2 m    |
| 15537    | CSE 3 HH 5e PUR; 3m, black     | 3 m    |
| 15538    | CSE 5 HH 5e PUR; 5m, black     | 5 m    |
| 15539    | CSE 10 HH 5e PUR; 10m, black   | 10 m   |
| 15540    | CSE 15 HH 5e PUR; 15m, black   | 15 m   |
| 15541    | CSE 20 HH 5e PUR; 20m, black   | 20 m   |

| TECHNICAL DATA      |   |
|---------------------|---|
| Cable type          | CAT 5e S/UTP  |
| Conductor area      | 19 x 0,15 mm <sup>2</sup> (AWG 26/19) stranded bare copper    |
| Conductor isolation | Solid PE (nom. 1,03 mm)                                       |
| Core assembly       | 4 twisted pairs   |
| Shielding type      | S/UTP   |
| Separator           | TPE-V stabilizer (inner jacket)                               |
| Max. CHANNEL-LINK   | CAT 5e (@ 100 MHz): 73 m                                      |
| Max. PERMANENT-LINK | CAT 5e (@ 100 MHz): 61 m                                      |
| PoE                 | IEEE 802.3af-2003; PoE (15,4W); max. Channel PoE (15,4W) 67 m |
| Overall screen      | tinned copper braid (85% nom. coverage)                       |
| Overall jacket      | PUR black   |
| Overall diameter    | 6,5 ± 0,2 mm  |
| Weight              | 56 kg/km  |