

# NEW CSE HH 6A PUR

CAT 6A cable suitable for audio networks  
and for EtherSound™ systems.

- highflex, resilient, reelable
- PUR jacket for mobile indoor/outdoor applications
- Plugs: 2x Telegärtner® RJ45, CAT6A, MFP8 IE
- Data category: CAT 6A (500 MHz)
- SF/UTP AWG 24

ITEM NO.	MATCH CODE	LENGTH
15608	CSE 1 HH 6A PUR; 1m, black	1 m
15609	CSE 1,5 HH 6A PUR; 1,5m, black	1,5 m
15610	CSE 2 HH 6A PUR; 2m, black	2 m
15611	CSE 3 HH 6A PUR; 3m, black	3 m
15612	CSE 5 HH 6A PUR; 5m, black	5 m
15613	CSE 10 HH 6A PUR; 10m, black	10 m
15614	CSE 15 HH 6A PUR; 15m, black	15 m
15615	CSE 20 HH 6A PUR; 20m, black	20 m

TECHNICAL DATA	
Cable type	CAT 6A SF/UTP
Conductor area	7 x 0,22 mm <sup>2</sup> (AWG 24) stranded bare copper
Conductor isolation	Solid PE (nom. 1,05 mm)
Core assembly	4 twisted pairs
Shielding type	SF/UTP
Pair screen	AL/PET foil
Separator	PE Separator-Cross
Max. CHANNEL-LINK	CAT 5e (@ 100 MHz): 90 m; CAT 6A (@ 500 MHz): 76 m
Max. PERMANENT-LINK	CAT 5e (@ 100 MHz): 76 m CAT 6A (@ 500 MHz): 64 m
PoE	IEEE 802.3bt-2018; PoE++ (99,9W); max. Channel PoE (99,9W) 64 m
Overall screen	tinned copper braid (85% nom. coverage) + AL/PET Tape
Overall jacket	Soft PUR black
Overall diameter	8,0 ± 0,3 mm
Weight	54 kg/km

