

NEW CSE HH-SD 6A PUR LONGRUN

CAT 6A cable suitable for audio networks
and for EtherSound™ systems.

- highflex, resilient, reelable
- PUR jacket for mobile indoor/outdoor applications
- Plugs: 2x Telegärtner® RJ45, CAT6A, MFP8 IE
- Data category: CAT 6A (500 MHz)
- S/FTP AWG 24
- Reeled on SCHILL® cable drums



ITEM NO.	MATCH CODE	LENGTH
15628	CSE 50 HH-SD 6A PUR LONGRUN; 50m, black	50 m
15629	CSE 75 HH-SD 6A PUR LONGRUN; 75m, black	75 m
15630	CSE 100 HH-SD 6A PUR LONGRUN; 100m, black	100 m

TECHNICAL DATA

Cable type	CAT 6A S/FTP
Conductor area	7 x 0,22 mm ² (AWG 24) stranded bare copper
Conductor isolation	Foam-Skin PE (nom. 1,4 mm)
Core assembly	4 twisted pairs
Shielding type	S/FTP
Pair Screen	AL/PET foil
Max. CHANNEL-LINK	CAT 5e (@ 100 MHz): 117 m; CAT 6A (@ 500 MHz): 103 m
Max. PERMANENT-LINK	CAT 5e (@ 100 MHz): 98 m CAT 6A (@ 500 MHz): 93 m
PoE	IEEE 802.3bt-2018; PoE++ (99,9W); max. Channel PoE (99,9W) 87 m
Overall screen	tinned copper braid (80% nom. coverage) + PET/PA fleece + drain wire
Overall jacket	Soft PUR black
Overall diameter	7,9 ± 0,3 mm
Weight	71 kg/km