

NEW CSE HH 7A PUR

CAT 7A cable suitable for audio networks
and for EtherSound™ systems.

- highflex, resilient, reelable
- PUR jacket for mobile indoor/outdoor applications
- Plugs: 2x RJ 45 HIROSE® TM31
- Data category: CAT 7A (1000 MHz)
- S/FTP AWG 26/7

ITEM NO.	MATCH CODE	LENGTH
15574	CSE 0,3 HH 7A PUR; 0,3m, black	0,3 m
15575	CSE 0,5 HH 7A PUR; 0,5m, black	0,5 m
15576	CSE 1 HH 7A PUR; 1m, black	1 m
15577	CSE 1,5 HH 7A PUR; 1,5m, black	1,5 m
15578	CSE 2 HH 7A PUR; 2m, black	2 m
15579	CSE 3 HH 7A PUR; 3m, black	3 m
15580	CSE 5 HH 7A PUR; 5m, black	5 m
15581	CSE 10 HH 7A PUR; 10m, black	10 m
15582	CSE 15 HH 7A PUR; 15m, black	15 m
15583	CSE 20 HH 7A PUR; 20m, black	20 m

TECHNICAL DATA

Cable type	CAT 7A S/FTP
Conductor area	7 x 0,14 mm ² (AWG 26/7) stranded bare copper
Conductor isolation	Foam-Skin PE (nom. 1,05 mm)
Core assembly	4 twisted pairs
Shielding type	S/FTP
Pair Screen	AL/PET Tape
Max. CHANNEL-LINK	CAT 5e (@ 100 MHz): 88 m; CAT 6A (@ 500 MHz): 77 m; CAT 7 (@ 600 MHz): 77 m; CAT 7A (@ 1000 MHz): 77 m;
Max. PERMANENT-LINK	CAT 5e (@ 100 MHz): 74 m; CAT 6A (@ 500 MHz): 66 m; CAT 7 (@ 600 MHz): 66 m; CAT 7A (@ 1000 MHz): 65 m;
PoE	IEEE 802.3af-2003; PoE (15,4W); max. Channel PoE (15,4W) 70m
Overall screen	tinned copper braid (65% nom. coverage)
Overall jacket	PUR black
Overall diameter	6,4 ± 0,2 mm
Weight	46 kg/km

