

NEW CSE NH 5e PUR

CAT 5e cable suitable for audio networks
and for EtherSound™ systems.

- highflex, resilient, reelable
- PUR jacket for mobile indoor/outdoor applications
- Plugs: 1x RJ 45 HIROSE® TM31 + 1x NEUTRIK® NE 8 MX-B-1
- Data category: CAT 5e (100 MHz)
- S/UTP 4x2x0,15 mm² AWG 26/19

ITEM NO.	MATCH CODE	LENGTH	LIST PRICE NET €*
15544	CSE 0,3 NH 5e PUR; 0,3m, black	0,3 m	21,50 €
15545	CSE 0,5 NH 5e PUR; 0,5m, black	0,5 m	22,32 €
15546	CSE 1 NH 5e PUR; 1m, black	1 m	24,35 €
15547	CSE 1,5 NH 5e PUR; 1,5m, black	1,5 m	26,39 €
15548	CSE 2 NH 5e PUR; 2m, black	2 m	28,43 €
15549	CSE 3 NH 5e PUR; 3m, black	3 m	32,51 €
15550	CSE 5 NH 5e PUR; 5m, black	5 m	40,86 €
15551	CSE 10 NH 5e PUR; 10m, black	10 m	61,34 €
15552	CSE 15 NH 5e PUR; 15m, black	15 m	82,39 €
15553	CSE 20 NH 5e PUR; 20m, black	20 m	108,18 €

*minus discount group RS2

TECHNICAL DATA

Cable type	CAT 5e S/UTP
Conductor area	19 x 0,15 mm ² (AWG 26/19) stranded bare copper
Conductor isolation	Solid PE (nom. 1,03 mm)
Core assembly	4 twisted pairs
Shielding type	S/UTP
Separator	TPE-V stabilizer (inner jacket)
Max. CHANNEL-LINK	CAT 5e (@ 100 MHz): 73 m
Max. PERMANENT-LINK	CAT 5e (@ 100 MHz): 61 m
PoE	IEEE 802.3af-2003; PoE (15,4W); max. Channel PoE (15,4W) 67 m
Overall screen	tinned copper braid (85% nom. coverage)
Overall jacket	PUR black
Overall diameter	6,5 ± 0,2 mm
Weight	56 kg/km

