

NEW CSE NN-SD 5e PUR LONGRUN

CAT 5e cable suitable for audio networks
and for EtherSound™ systems.

- highflex, resilient, reelable
- PUR jacket for mobile indoor/outdoor applications
- Plugs: 2x NEUTRIK® NE 8 MX-B-1
- Data category: CAT 5e (100 MHz)
- SF/UTP AWG 24/1
- Reeled on SCHILL® cable drums



ITEM NO.	MATCH CODE	REELED TO
15570	CSE 25 NN-SD 5e PUR LONGRUN; 25m, black	25 m
15571	CSE 50 NN-SD 5e PUR LONGRUN; 50m, black	50 m
15572	CSE 75 NN-SD 5e PUR LONGRUN; 75m, black	75 m
15573	CSE 100 NN-SD 5e PUR LONGRUN; 100m, black	100 m

TECHNICAL DATA

Cable type	CAT 5e SF/UTP
Conductor area	1 x 0,20 mm ² (AWG 24/1) solid bare copper
Conductor isolation	Foam-Skin PE (nom. 1,02 mm)
Core assembly	4 twisted pairs
Shielding type	SF/UTP
Separator	PE Separator-Cross
Max. CHANNEL-LINK	CAT 5e (@ 100 MHz): 117 m
Max. PERMANENT-LINK	CAT 5e (@ 100 MHz): 98 m
PoE	IEEE 802.3af-2003; PoE (15,4W); max. Channel PoE (15,4W) 103 m
Overall screen	tinned copper braid (82% nom. coverage) + AL/PET Tape
Overall jacket	PUR black
Overall diameter	6,8 ± 0,2 mm
Weight	57 kg/km