

NEW CSE NN-SD 5e PUR

CAT 5e cable suitable for audio networks
and for EtherSound™ systems.

- highflex, resilient, reelable
- PUR jacket for mobile indoor/outdoor applications
- Plugs: 2x NEUTRIK® NE 8 MX-B-1
- Data category: CAT 5e (100 MHz)
- S/UTP AWG 26/19
- Reeled on SCHILL® cable drums



ITEM NO.	MATCH CODE	LENGTH
15564	CSE 25 NN-SD 5e PUR; 25m, black	25 m
15565	CSE 50 NN-SD 5e PUR; 50m, black	50 m

TECHNICAL DATA	
Cable type	CAT 5e S/UTP
Conductor area	19 x 0,15 mm ² (AWG 26/19) stranded bare copper
Conductor isolation	Solid PE (nom. 1,03 mm)
Core assembly	4 twisted pairs
Shielding type	S/UTP
Separator	TPE-V stabilizer (inner jacket)
Max. CHANNEL-LINK	CAT 5e (@ 100 MHz): 73 m
Max. PERMANENT-LINK	CAT 5e (@ 100 MHz): 61 m
PoE	IEEE 802.3af-2003; PoE (15,4W); max. Channel PoE (15,4W) 67 m
Overall screen	tinned copper braid (85% nom. coverage)
Overall jacket	PUR black
Overall diameter	6,5 ± 0,2 mm
Weight	56 kg/km